





Li-Ion's roar: Unleashing the potential of battery simulation




Development Cycle – various requirements




Flavors of Battery Modeling



Flavors of Battery Modeling





Bulk-Surface model




- P2D model, a set of coupled partial differential equations (PDEs)

AutoLion-RT







- Converting PDEs into ODE set
- Considering instantaneous diffusion between electrodes

Hardware-in-the-Loop Simulations




AutoLion-RT



Value Add:



Improved support for controls teams, who rely heavily on electrical-equivalent solutions today

Flavors of Battery Modeling





Beyond P2D


- Material Properties Database
- Physics based models of degradation
- Integrated Multi-Domain Systems
- Thermal included - one thermal node
- Blend electrodes & particle size distribution




- Properties**
- Material Properties**
- Mol. Weight, Density, Capacity
 - Open-Circuit Potential
 - Diffusivity
 - Rate Constants
- Electrolyte Properties**
- Conductivity
 - Diffusivity




Flavors of Battery Modeling



Introduction to GT-AutoLion-3D




P2D electrochemical-thermal model



P3D electrochemical-thermal model

Introduction to GT-AutoLion-3D



P3D electrochemical-thermal model

Electrical Solution: Resistor network for current collectors


Electrochemical Solution: AutoLion-1Ds in parallel

- Same underlying solution (including aging models)

Thermal Solution: GT-SUITE's 3D finite element solution

- Anisotropic properties
- Ability to connect to other parts (i.e., case)
- Ability to connect to flow domain
- GEM-3D support


Introduction to GT-AutoLion-3D



P3D electrochemical-thermal model

2D/quasi-3D Electrochemical results:


- Current
- Voltage
- Heat Generation
- Aging
- State of Charge
- Stoichiometry



Current Distribution
(unrolled JR, cylindrical and prismatic)


3D Thermal results:

- Temperature




GT-AutoLion-3D Use Cases

- Detailed Cell Modeling
 - Tab modeling, form factors
- Inhomogeneities ask for discretization
 - Extreme Operating Conditions (Load and Temperature)
 - Lithium Plating and Fast Charging Capability Analysis
 - Cell Cooling Design and Optimization
- Safety Events Analysis (Internal Short, Nail Penetration)
- Cell Swelling




Model Results: Thermal Behavior

Constant current discharge process at the temperature of 0 °C – 1C rate




$T = 5.81 \text{ C @ } t = 1300 \text{ s}$

Single value across the cell!




Temperature distribution across the cell!

Flavors of Battery Modeling





Anode Overhang


AutoLion-4D



Simulation Results




True 3D Diffusion
"Edge Effects" with AL-4D




15 IAV 10/2023 US-15 Reik Laubenstein Status: Released, public. Do not hand over to third parties without written permission.





User-Defined Reactions



Template: SpeciesList

This is a Beta template in V2024.

Connectivity Information Show Examples Help

Default Ignore Show Value Attribute Abilities

Formula Editor [-] Create Parameter

Object Comment: Part Comment: Add Long Comment Comments

Object Usage

Hide Unused Objects?

- eu-4d_species
 - AutoLion-4D
 - AutoLion-4D
 - Species Settings Object

Attri...	Solid Species Name	Solid Species Reference Object	Export Species Profile and 2d/3d plots
1	C6	C6	<input type="checkbox"/>
2	LiC6	LiC6	<input type="checkbox"/>
3	FePO4	FePO4	<input type="checkbox"/>
4	LiFePO4	LiFePO4	<input type="checkbox"/>
5	(CH2OCCO2)2	SEI	<input type="checkbox"/>
6	Li2CO3	SEI	<input type="checkbox"/>
7	Li_s	Li_metal_deposit	<input type="checkbox"/>
8	Li_s_rev	Li_metal_reversible	<input type="checkbox"/>
9			<input type="checkbox"/>
10			<input type="checkbox"/>
11			<input type="checkbox"/>
12			<input type="checkbox"/>
13			<input type="checkbox"/>
14			<input type="checkbox"/>
15			<input type="checkbox"/>
16			<input type="checkbox"/>
17			<input type="checkbox"/>
18			<input type="checkbox"/>
19			<input type="checkbox"/>
20			<input type="checkbox"/>
21			<input type="checkbox"/>
22			<input type="checkbox"/>
23			<input type="checkbox"/>
24			<input type="checkbox"/>

Object Usage

Hide Unused Objects?

- Cell_interface
 - AutoLion-4D
 - AutoLion-4D
 - Cell Interface Object


Deposits

Attribute	Object Value
MAIN	
Number of Deposits	4
Number of Reactivities	3
Reactivity 1	SEI_formation
Reactivity 2	Li_plating
Reactivity 3	Li_stripping


Attribute	Unit	Deposit #1	Deposit #2	Deposit #3	Deposit #4
Deposit Species Properties					
Deposit Species Name		(CH2OCCO2)2	Li2CO3	Li_s	Li_s_rev
Thermal Conductivity	W/(m-K)	0.1	0.1	84.8	84.8
Specific Heat Capacity	J/kg-K	1510.0	1510.0	1510.0	1510.0
Electrical Conductivity	S/m	5.0E-6	5.0E-6	1.17E7	1.17E7
Formation Density	kg/m^3	1690.0	1500.0	534.0	534.0
Porosity	fraction	0.05	0.05	0.05	0.05
Sluggishness Exponent		1.5	1.5	1.0	1.0
Initial Conditions					
Initial Amount	mol/m^3	0.0	0.0	0.0	0.0
Initial Axial Distribution	kg	kg	kg	kg	kg




Flavors of Battery Modeling




Different Flavours of Battery Modeling





Integrated Multi-Domain Modelling


AutoLion-1D Real-world Aging




Physics-based aging models



Full System Model



Commuting / Usage Patterns



Weather Patterns




Charging Patterns

*More meaningful aging predictions
(Miles, Years of operation)*


Vehicle/Powertrain Model

- Electrical Load on cell calculated based on vehicle „operating point“
- Low Voltage circuit with consumers
- Electrical domain allowing for modeling of
 - BMS, cell balancing over module
 - Circuit Protection



Model Setup for a Single Cell


- A compound was created with the following architecture
- GT-AutoLion cell & 3D thermal finite element cell exchange heat rate and temperature through control objects
- Gases ejected from TR pass through a pressure release valve through the ambient where combustion occurs
- Heat generated from the combustion of gases is also fed back to the battery pack



Mechanical Connectivity

In addition to cell performance (Voltage, Heat Generation), GT-AutoLion can predict stress & strain on a cell


Interaction with Aging




- Active material in cathode
- Active material in anode
- Lithium-ion (Li⁺)

Mechanical Connectivity


Example Cell in Module Casing Slot



Electrochemical-Mechanical Model





Cell Swelling during charge



Stress/Strain on Casing
-> Impact on Cell Performance


Solid-State Batteries




▪ SSB related features includes:

- Defining different electrolytes for anolyte, solid separator, and catholyte
- Modelling capability of reaction surface area
- Einstein's relationship for ionic diffusivity
- Defining multiple layer of solid separators in contact with Li metal anode
- Multiple solid electrolytes support

Types of solid electrolytes




Sodium-Ion Batteries




Sodium-Ion Batteries


- Material Properties Database
 - Anode materials: Hard Carbon
 - Cathode material: $\text{Na}_3\text{V}_2(\text{PO}_4)_2\text{F}$ (NVPF)
 - Electrolyte: NaPF_6 in $\text{EC}_{0.5}:\text{PC}_{0.5}$ (w/w)
- Physics based models of degradation
- Blend electrodes & particle size distribution



Conclusion



Perspectives - Connectivity



Different Flavors - Flexibility

Ready for the future



Thanks for listening...hungry?



Source: <https://www.ast-reisen.de/tiere-afrikas/loewe/>